

PRODUCT INFORMATION



The classic Diamond[®] retaining wall system is the contractor's choice for wall construction. Straight- or beveled-face shapes provide design freedom. Optional step and cap accessories offer even more design versatility. For an attractive retaining wall with enduring performance, the Diamond product is the perfect choice.

- Patented rear-lip technology
- Build gravity walls up to 4 feet, 6 inches high, including buried course
- Taller walls can be built using geosynthetic reinforcement or stabilized aggregate when designed by a qualified engineer
- ICC evaluated



Visit anchorwall.com for installation instructions.

*Actual dimensions and weight may vary from these approximate dimensions due to variations in manufacturing processes. Specifications may change without notice. See your Anchor representative for details, color options, block dimensions and additional information.



Stretcher Units

Beveled Face

Straight Face

Approximate Dimensions*	6" x 15 ⁷ / ₈ " x 12"	6" x 17 ¹ / ₄ " x 12"
Approximate Weight	68 lbs.	72 lbs.
Coverage	.67 sq. ft.	.72 sq. ft.
Setback/Batter	1 ¹ / ₈ " / 10.6°	1 ¹ / ₈ " / 10.6°
Minimum Inside Radius	2'	4'
Minimum Outside Radius	4'	8'



Accessory Units

Cap

Step

Approximate Dimensions*	Front, 3" x 17 ¹ / ₄ " x 10" Back, 3" x 12" x 10"	6" x 16" x 12"
Approximate Weight	32 lbs.	85 lbs.
Coverage	1.22 linear ft.	

© 2009 Anchor Wall Systems, Inc. The Diamond[®] wall system is manufactured under license from Anchor Wall Systems, Inc. (AWS). The "Anchor Build Something Beautiful" logo and "Diamond" are trademarks of AWS. The wall system blocks are covered by the AWS Limited Warranty. For a complete copy, visit your local dealer or see anchorwall.com.

Anchor Wall Systems, Inc., 5959 Baker Road, Suite 390, Minnetonka, MN 55345.
A&B0810

L880 05/09