



HP and RG MASONRY ADHESIVES

for WALLS, PAVERS AND SLABS

300 mL and 858 mL

300 mL

UPDATE

July 16, 2003

Make sure that you have an up-to-date technical data sheet at hand.

Canada and U.S.A.: dial 1-800-465-7325.

Others: dial 514-523-8324 (Canada).

www.techniseal.com

APPLICATIONS

- Retaining walls, pavers and slabs
- Any concrete or masonry surface

DESCRIPTION

Specially formulated for the construction of concrete hardscapes, TECHNI-SEAL adhesives are first-quality products designed to resist the elements (water, frost, etc.). They provide a strong and durable bond.

DISTINCTIVE FEATURES

HP MASONRY ADHESIVE: high-tech product made of moisture-cure urethane, i.e., which cures quickly by reacting with ambient humidity. Flexible and as solid as the material, it is ideal for use in heavy traffic areas (sidewalks, steps, etc.). It adheres to most materials (concrete, wood, metal, etc.). Stronger than regular adhesives, it allows one to use less product for equal results. Low in volatile organic compounds (V.O.C.), it does not give off strong fumes and it is environmentally friendly.

RG MASONRY ADHESIVE: elastomeric-resin-based compound. Remaining flexible, it is ideal for the construction of retaining walls. Most effective on dry surfaces. Can also be used on wet or frozen surfaces (allow for longer curing period). More economical than HP ADHESIVE.

DIRECTIONS

Read the Material Safety Data Sheet before using this product. Wear adequate protective clothing.

HP: Temperature should be above 5°C (40°F). Surface should be clean and dry. Wear gloves. Apply a maximum thickness of 1 cm (3/8"). Drying time will vary depending on ambient humidity.

RG: Surface should be clean and, ideally, dry. Apply a maximum thickness of 1 cm (3/8"); join pieces together immediately with a slight twisting motion.

COVERAGE

1 litre makes a bead 1cm (0.4") in diameter by 10 to 11 linear metres (32 to 36 linear feet).

PACKAGING

Name	Product Code	Size	Units by box	Units per pallet
HP	141-711	300 mL	24	1,152
RG	141-721	300 mL	12	1,296
RG	141-722	858 mL	12	456

300 mL = 10.15 U.S. fl. oz.
858 mL = 29 U.S. fl. oz.

SHIPPING

Land and Sea

HP:

••• Not regulated

RG:

ADHESIVES containing flammable liquid

Class : 3
UN Number : 1133
Packing Group : III
(Limited Quantity)

LIMITED WARRANTY: Since it has no control over surface preparation and product application, Techni-Seal can not guarantee the results. Techni-Seal's warranty is limited to the replacement or reimbursement of product proven defective. Note: User should have an up-to-date technical data sheet handy and make sure that this product meets his or her needs by carrying out a test under anticipated conditions of use.