



2L



RUST REMOVER

for PAVERS AND SLABS

UPDATE

February 27, 2003

Make sure that you have an up-to-date technical data sheet at hand.

Canada and U.S.A.: dial 1-800-465-7325.

Others: dial 514-523-8324 (Canada).

www.techniseal.com

APPLICATIONS

- Sealed or bare surfaces.
- Pavers and slabs made of concrete or natural stone, masonry, etc.
- Concrete, clay, stone, marble, granite, slate, etc.
- Driveways, pool decks, patios, terraces, commercial parking lots, pedestrian areas, buildings, etc.

DESCRIPTION

TECHNI-SEAL RUST REMOVER takes out rust from concrete or natural stone pavers and slabs. It effectively dissolves stains caused by dripping rusted water, steel streaks, fertilizer granules¹, etc. Containing no hydrochloric (muriatic) acid, it won't discolour the material.

¹To remove fertilizer stains from a large surface, it is recommended to use TECHNI-SEAL EFFLORESCENCE CLEANER (141-534, 241-537).

DIRECTIONS

Read the Material Safety Data Sheet before using this product. Wear adequate protective clothing. Wet the stain and cover it generously with RUST REMOVER; using a SMALL TECHNI-SEAL BRUSH, scrub the stain until dissolved; rinse immediately with water. If rust persists, repeat the operation.

NOTE

Pavement with efflorescence (whitish salt) will appear spotted after the use of RUST REMOVER; for uniform results, finish by cleaning the entire surface with EFFLORESCENCE CLEANER (141-534/241-537). Rust streaks caused by snowplough rubbing may be difficult to remove.

PACKAGING

Product Code	Retail Size	Units per box	Units per pallet
141-522	2L	6	216

2L = 2 U.S. qt.

SHIPPING

Land and Sea

Phosphoric Acid in Solution
 Class : 8 (9.2)
 UN Number : 1805
 Packing Group : III
 Flash Point : n/a

LIMITED WARRANTY: Since it has no control over surface preparation and product application, Techni-Seal can not guarantee the results. Techni-Seal's warranty is limited to the replacement or reimbursement of product proven defective. Note: User should have an up-to-date technical data sheet handy and make sure that this product meets his or her needs by carrying out a test under anticipated conditions of use.