



WATER REPELLENT

for WALLS, PAVERS AND SLABS

3.78L

UPDATE

July 16, 2003

Make sure that you have an up-to-date technical data sheet at hand.

Canada and U.S.A.: dial 1-800-465-7325.

Others: dial 514-523-8324 (Canada).

www.techniseal.com

FUNCTION

- Repels water and dirt
- Protects against salt and frost
- Prevents the appearance of efflorescence
- Invisible and penetrating
- Allows breathing

DESCRIPTION

Made of siloxanes, TECHNI-SEAL WATER REPELLENT FOR WALLS, PAVERS AND SLABS provides excellent protection against water, dirt, salt (calcium) and freeze-thaw cycles. Its active agents (siloxanes) penetrate deeply and chemically react with the material to form an invisible and durable protection. TECHNI-SEAL WATER REPELLENT FOR RETAINING WALLS, PAVERS AND SLABS lets the material breathe and prevents the formation of efflorescence (whitish salt).

DIRECTIONS

Note : The reaction of siloxanes with the material extends over thirty days or so; product’s effectiveness will therefore be more perceptible after this period.

Surface preparation: Clean the surface with TECHNI-SEAL EFFLORESCENCE CLEANER FOR PAVING STONES (141-534/241-537).

Application: Read the Material Safety Data Sheet before using this product. Wear adequate protective clothing. For best results, ambient temperature should be between 10°C (50°F) and 25°C (77°F). The surface to be treated must be dry, porous and clean. Surfaces not to be treated, such as windows, doors, aluminum surfaces, wood panelling, greenery, etc., should be protected from splashing or spilling. Apply WATER REPELLENT using a paint brush, a foam roller for rough surfaces (19 mm thickness) or a mineral spirits-resistant sprayer. Working from top to bottom, apply one coat of WATER REPELLENT, soaking the surface until product takes at least 15 seconds to be absorbed.

NOTE

In some cases the treatment may darken the colour of the material. It is recommended that a small area be tested prior to application. This product reacts with moisture; store in a very dry place until use.

COVERAGE

1 litre covers up to 1.85 m² (20 sq. ft.). The quantity required depends on the porosity of the material to be treated. It is recommended that a small area be tested to determine the exact amount needed.

PACKAGING

Product Code	Retail Size	Units per box	Units par pallet
141-283	3.78 L	4	240

3.78 L = 1 U.S.gal.

SHIPPING

Land and Sea

••• Not regulated

Packing Group : III
 Flash Point : > 37.8°C (100°F)
 Small means of containment : ≤ 454L (100 gal.)

LIMITED WARRANTY: Since it has no control over surface preparation and product application, Techni-Seal can not guarantee the results. Techni-Seal’s warranty is limited to the replacement or reimbursement of product proven defective. Note: User should have an up-to-date technical data sheet handy and make sure that this product meets his or her needs by carrying out a test under anticipated conditions of use.